



Specification:

	TM-U220A with paper roll reeler and paper cutter	TM-U220B with paper cutter	TM-U220D basic version
Means of print	9-needle		
Fonts	7 × 9 / 9 × 9 points		
Quantity of characters in one line	paper 76,0 mm: 42/40/35/33 cpl	69,5 mm: 40/36/32/30 cpl	57,5 mm: 33/30/27/25 cpl
Character dimensions (mm)	1,2 / 1,6 / 1,7 / 1,9 / 2,0(width) x 3,1(height)		
Quantity of characters per inch	17,8 / 16 / 14,5 / 13,3		
Interfaces	RS-232 or parallel or USB or Ethernet drive for cassette drawers, power adapter connection		
Input buffer	1 kB or 40 bytes		
Memory for logo	128 kB		
User defined memory	8 kB		
Print speed	6 lines / second (30 characters / line)		
Paper width	76,0 mm +/- 0.5	69,5 mm +/- 0.5	57,5 mm +/- 0.5
Paper roll diameter	maximally 83 mm		
Colouring tape	ERC-38 purple, black or red-black		
Paper cutter	Cutter type "full cut" or "one-point-left cut" built in models type A and B		
Power consumption	Stand-by: 2,2 W while printing: 31 W		
Power adapter	included (compatible with PS-180)		
Cassette drawers	drive for two cassette drawers		
Durability	MTBF: 180 000 hours MCBF: 18 million lines cutter: 800 000 cuts		
Dimensions	160 x 286 x 158 mm	160 x 248 x 139 mm	160 x 248 x 139 mm
Weight	2,7 kg	2,5 kg	2,3 kg
Colours	white: EPSON cool white or dark grey: EPSON dark grey		
Standard functions	paper reeler (type A) paper cutter (type A and B) easy paper exchange type "Drop-in" built in function Auto Status Back paper end sensor, paper end sensor, power adapter		
Options	wall hanger (for type B) customer display DM-D (connected through interface UB-S09)		
Standard EMI	sign CE, EN55022 class B, EN55024		
Safety standards	EN60950		